

T17C2M

Engine MITSUBISHI , S4Q2-Z261SD
 Alternator MECC ALTE , ECO28VL

STANDARD FEATURES

- Mechanic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for wiring temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 12 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
240 MONO	17 / 17	15.5 / 15.5	71		
230 MONO	17 / 17	15.5 / 15.5	74	Leng : 1700mm [67in] Widt : 896mm [35in]	580kg [1279lbs] Net 680kg [1499lbs] Gross
220 MONO	17 / 17	15.5 / 15.5	77	Heig : 1121mm [44in]	



POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions ESP/PRP 25 C°/25 C° Air Intlet Temp, 100 m/100 m m A.S.L. 60 % relative humidity.

Model	dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
 M127-DW	71	61	Leng : 2160mm [85in] Widt : 966mm [38in] Heig : 1582mm [62in]	991kg [2185lbs] 1221kg [2692lbs]	230 L
 M127	71	61	Leng : 2080mm [82in] Widt : 960mm [38in] Heig : 1415mm [56in]	810kg [1786lbs] 910kg [2006lbs]	100 L

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products.

OCKTcom Limited

Unit 2 Bird Business Park, Station Road, Long Marston, Nr Stratford upon Avon, Warwickshire CV37 8RP

Tel: 01789 722330 Fax: 01789 722332 Email: info@ocktcom.com

www.ocktcom.com

Company Registration No. 3138035

 SDMO Gold Dealer