

T6KM

Engine MITSUBISHI , L3E-SD
Alternator MECC ALTE , ECO3-2S

STANDARD FEATURES

- Mechanic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for wiring temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 12 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
240 MONO	5.5 / 5.5	5 / 5	23		
230 MONO	5.5 / 5.5	5 / 5	24	Leng : 1220mm [48in]	280kg [617lbs] Net
220 MONO	5.5 / 5.5	5 / 5	25	Widt : 700mm [28in] Heig : 922mm [36in]	330kg [728lbs] Gross


POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions ESP/PRP 25 C°/25 C° Air Intlet Temp, 100 m/100 m m A.S.L. 60 % relative humidity.

Model	dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
 M125	69	59	Leng : 1482mm [58in] Widt : 760mm [30in] Heig : 1030mm [41in]	390kg [860lbs] 440kg [970lbs]	50 L

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products.

OCKTcom Limited

Unit 2 Bird Business Park, Station Road, Long Marston, Nr Stratford upon Avon, Warwickshire CV37 8RP

Tel: 01789 722330 Fax: 01789 722332 Email: info@ocktcom.com

www.ocktcom.com

Company Registration No. 3138035

 SDMO Gold Dealer