

T9KM

Engine MITSUBISHI , S3L2-SD
Alternator MECC ALTE , ECO3-3LN

STANDARD FEATURES

- Mechanic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for wiring temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 12 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
240 MONO	8.6 / 8.6	7.8 / 7.8	36		
230 MONO	8.6 / 8.6	7.8 / 7.8	37	Leng : 1405mm [55in]	396kg [873lbs] Net
220 MONO	8.6 / 8.6	7.8 / 7.8	39	Widt : 715mm [28in] Heig : 1053mm [41in]	447kg [985lbs] Gross



POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions ESP/PRP 25 C°/25 C° Air Intlet Temp, 100 m/100 m m A.S.L. 60 % relative humidity.

Model	dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
 M126-DW	70.4	60.4	Leng : 1797mm [71in] Widt : 775mm [31in] Heig : 1391mm [55in]	625kg [1378lbs] 709kg [1563lbs]	93 L
 M126	70.4	60.4	Leng : 1750mm [69in] Widt : 775mm [31in] Heig : 1230mm [48in]	544kg [1199lbs] 595kg [1312lbs]	50 L

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products.

OCKTcom Limited

Unit 2 Bird Business Park, Station Road, Long Marston, Nr Stratford upon Avon, Warwickshire CV37 8RP

Tel: 01789 722330 Fax: 01789 722332 Email: info@ocktcom.com

www.ocktcom.com

Company Registration No. 3138035

 SDMO Gold Dealer